

Polarization Insensitive Isolator 2000nm

Features	
Low Insertion Loss High Power Handling High Isolation Low PDL Low Cost	
Application	
Optical Fiber Amplifier Fiber Optic Sensor Instrumentation R&D Fiber Lasers Radar	


Specifications

Parameter	Value	
	Single Stage	Dual Stage
Stage		
Center wavelength(nm)	2000	
Bandwidth(nm)	±50	
Isolation at λ_c 23°C (dB)	≥20	≥35
Typ. Insertion Loss at 23°C (dB)	0.8	1.0
Insertion Loss at 23°C (dB)	≤1.0	≤1.2
PDL (dB)	≤0.15	≤0.20
Return loss (Input/output) (dB)	≥50/50	≥50/50
PMD(ps)	≤0.20	≤0.05
Power handling (mW)	≤500	
Tensile Load(N)	≤5	
Fiber Type	SMF-28e Fiber , SM 1950 Fiber or Specify	
Operating temperature (°C)	-5 ~ +70	
Storage temperature (°C)	-40 ~ +85	
Package(mm)	φ5.5×L35	

*Above specifications are for devices without the connectors.

*For devices with connectors, IL will be 0.3dB higher and RL will be 5dB lower.

Package Dimensions



Ordering Information

IS	Type	Wave length	Pigtail Type	Fiber Type	Length	Connector	Package size
	S= Single stage D= Dual Stage	2000	250=250um bare fiber 900=900um loose tube 3000=3mm loose tube	1=SMF-28e 9=SM 1950	0.8=0.8 1= 1m	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC XX=Other	5.5x35